CC6100/CC6150 Series

Coin Changer Series

- Easily configurable payout system with modular tube design.
- Six circulating coin tubes for a higher coin capacity and lower restocking frequency.
- High performance coin management system.
- Advanced anti-counterfeiting technology.
- Support EVA-DTS auditing format. CC6100SA/CC6100E
- IrDA firmware upgrade available. CC6100SA/CC6100E
- Power saving function. CC6100SA
- Supports large-coin acceptance up to 32 mm in diameter. CC6150



CC6100

CC6150

ICT

CC6100/CC6150 Series

Coin Changer Series

The Coin Changer Series features six modular coin tubes to provide the highest level of flexibility in managing payout combinations. With MDB, JPSTD and Executive/ MDB interfaces available, the Coin Changer Series supports multiple and outdoor applications.

Specifications

Acceptance Rate
96% or greater

Coin Accepted
CC6100
Diameter : 16~28 mm/0.63~1.10 inches
Thickness: 1.2~3.2 mm/0.05~0.13 inches

CC6150
Diameter : 16~32 mm/0.63~1.26 inches
(large coin goes to coin box)
Thickness: 1.2~3.2 mm/0.05~0.13 inches

Acceptance Speed
Approx. 1 coin/sec.

Number of tubes
6

Interface
MDB (CC6100/CC6150)
JPSTD (CC6100)
Executive/MDB (CC6100)

Power Source
MDB: 20V DC ~ 45V DC
MDB: 10V DC ~ 45V DC (CC6100SA)
JPSTD: 24V DC ±10%
Executive: 24V AC ±10%

Power Consumption
Standby mode: ≤3.6W
Coin acceptance: ≤15.6W
Coin payout: ≤15.6W
(36W max. when Power is turned on initially)

Battery operation (Power Saving Type)
Sleep mode: ≤10uA
Standby mode: ≤3.6W(wake-up mode)

Dimension
(H)370.5 x (W)140.6 x (D)82.5 mm/
(H)14.58 x (W)5.53 x (D)3.24 inches

Weight
Approx. 2.05 kg/4.4 lbs

Environmental
Operating Temperature: -15°C/5°F~60°C/140°F
Storage Temperature: -30°C/-22°F~70°C/158°F
Humidity: 30%~85%RH(no condensation)


Escrow <Optional>
2 coins/ 1 channel

Recommended Applications
Indoor/Outdoor Vending, Kiosk

⊙ Please refer to ICT website (www.ictgroup.com.tw) for tube assignment.
⊙ JPSTD stands for Japan standard communication interface.

Specifications are subject to change without prior notice.







International Currency Technologies
No.28, Ln. 15, Sec. 6, Minquan E. Rd., Neihu Dist., Taipei City 114, Taiwan
Phone: +886-2-2793-1236
Fax: +886-2-2793-6125
EMail: sales@ictgroup.com.tw (Product Information)
fae@ictgroup.com.tw (Technical Service)
Website: www.ictgroup.com.tw

A07ENFLCC-CC6100/6150S26